



FED-X S/S Four Door Upright Fridge - XURC1200S2V

Quick Overview

- Gross Volume: 1236L
- Net Volume: 791L
- Max Ambient Temperature: 43°C, 60%RH
- Temperature Range: -2 to +8°C
- Cooling System: Fan-Forced cooling
- Controller: Dixell
- Refrigerant: R290
- Stainless steel interior and exterior with rounded corners for easy cleaning
- Auto defrost
- Three levels of shelving plus base
- Self-closing lockable doors with heavy-duty magnetic door seals
- HFCs and CFCs free foam body insulation
- Tropicalised for Australian conditions
- User-friendly Digital controls and internal lighting
- Split door design for rapid recovery and energy-saving
- Integrated door handle for easy cleaning
- Shelf and shelf support are designed to accommodate 2 x 1/1 GN pan
- Heavy-duty evaporator and condenser fans
- Heavy-duty castors with front-wheel brakes
- Weight loading per shelf: 40kg
- Dimensions (Internal): 1224mm W x 682mm D x 1394mm H
- 1/2 split door system can lower yearly running costs by up to 30%

Description

FED-X S/S Four Door Upright Fridge - XURC1200S2V

Key Features

- Gross Volume: 1236L
- Net Volume: 791L
- Max Ambient Temperature: 43 °C, 60%RH
- Temperature Range: -2 to +8 °C
- Cooling System: Fan-Forced cooling
- Controller: Dixell
- Refrigerant: R290
- Stainless steel interior and exterior with rounded corners for easy cleaning
- Auto defrost
- Three levels of shelving plus base
- Self-closing lockable doors with heavy-duty magnetic door seals
- HFCs and CFCs free foam body insulation
- Tropicalised for Australian conditions
- User-friendly Digital controls and internal lighting
- Split door design for rapid recovery and energy-saving
- Integrated door handle for easy cleaning
- Shelf and shelf support are designed to accommodate 2 x 1/1 GN pan
- Heavy-duty evaporator and condenser fans
- Heavy-duty castors with front-wheel brakes
- Weight loading per shelf: 40kg
- Dimensions (Internal): 1224mm W x 682mm D x 1394mm H
- 1/2 split door system can lower yearly running costs by up to 30%

2 Years Parts and Labour + 2 Years Parts only Warranty with Product Registration within 14 Days of Invoice

Your Shipping Specifications

Doors	4
Door Type	Hinged Doors
Body	Stainless Steel
Gross Volume	1236L
Net Volume	791L
Max Ambient Temperature	43 , 60%RH
Temperature Range	-2 to +8 ° C
Total Energy Consumption	3.62 kWh/24h
Net Weight (Kg)	167
Width (mm)	1340
Depth (mm)	810+30
Height (mm)	2000
Packing Width (mm)	1365
Packing Depth (mm)	855
Packing Height (mm)	2150
Power	240V, 430W/10A
Warranty	2 Years Parts and Labour + 2 Years Parts Only for Products Registered within 14 Days of Invoice