



## Fagor EVO-CONCEPT Pass-through Dishwasher - CO-142HRBDD

### Quick Overview

- Hood-type dishwashers with heat recovery system
- EVO Generation
- Constructed in stainless steel.
- Counterbalanced hood with handle and spring system.
- Stainless steel double rotating wash and rinse system, top and bottom.
- 440 mm hood opening (suitable for GN 1/1 trays).
- Continuous wash cycle.
- High water flow wash pump
- Rounded tank to facilitate washing and drainage.
- Stainless steel armored heating elements in the wash tank and rinse boiler.
- (Optional) Multi-voltage: Allows the machine to be connected to a single-phase or three-phase voltage network.
- AISI-304 stainless steel filter trays in the wash tank.
- Thermostatic controlled temperatures (wash, 60° C, and rinse, 90° C).
- Thermal stop system which guarantees a rinse temperature of 85° C.
- Safety stop switch in hood opening.
- Safety thermostat - Machine with control panel and electronic control
- 55°&#x9D;,, 75°&#x9D; and 120°&#x9D; wash cycles.
- Theoretical maximum production of 65 baskets/hour (1170 plates/h).
- 2.4-litre water consumption per cycle.
- Rinse with a thermostat system.
- Standard factory setting disabled. Easy to enable.
- Alternating or simultaneous tank and boiler heating.
- IPX4 anti-humidity protection.
- Energy recovery device
- Drainage pump
- Tank emptying program.
- Peristaltic detergent doser.
- Equipment included: One base basket, one basket for plates and two cutlery holder
- Water mark certified product sticker

### Description

Fagor EVO-CONCEPT Pass-through Dishwasher - CO-142HRBDD

## Key Features

- Hood-type dishwashers with heat recovery system
- EVO Generation
- Constructed in stainless steel.
- Counterbalanced hood with handle and spring system.
- Stainless steel double rotating wash and rinse system, top and bottom.
- 440 mm hood opening (suitable for GN 1/1 trays).
- Continuous wash cycle.
- High water flow wash pump
- Rounded tank to facilitate washing and drainage.
- Stainless steel armored heating elements in the wash tank and rinse boiler.
- (Optional) Multi-voltage: Allows the machine to be connected to a single-phase or three-phase voltage network.
- AISI-304 stainless steel filter trays in the wash tank.
- Thermostatic controlled temperatures (wash, 60 ° C, and rinse, 90 ° C).
- Thermal stop system which guarantees a rinse temperature of 85 ° C.
- Safety stop switch in hood opening.
- Safety thermostat - Machine with control panel and electronic control
- 55 " , 75 " and 120 " wash cycles.
- Theoretical maximum production of 65 baskets/hour (1170 plates/h).
- 2.4-litre water consumption per cycle.
- Rinse with a thermostat system.
- Standard factory setting disabled. Easy to enable.
- Alternating or simultaneous tank and boiler heating.
- IPX4 anti-humidity protection.
- Energy recovery device
- Drainage pump
- Tank emptying program.
- Peristaltic detergent doser.
- Equipment included: One base basket, one basket for plates and two cutlery holder
- Water mark certified product sticker

## Certified Product



Your Shipping Specifications

Net Weight (Kg)	126
Width (mm)	630
Depth (mm)	750
Height (mm)	2000
Packing Width (mm)	905
Packing Depth (mm)	825
Packing Height (mm)	1720
Power	11.1/3~N kW/A
Warranty	2 Years Parts and Labour