



Bonvue Chilled Angled Counter-Top Food Display - CTA-196

Quick Overview

- **Eco-Friendly Efficiency:** Utilizes natural R290 refrigerant, with an exceptional 9 or 10-star GEMS energy rating
- **Enhanced Product Showcase:** Offers a larger display area than competitors, featuring an additional shelf for more display space
- **Bright LED Lighting:** Dual-sided LED lights create an attractive presentation of contents
- **Precision Temperature Control:** Digital temperature controller for accurate adjustments
- **Extra Shelving Advantage:** Comes with three adjustable chrome-plated shelves, maximizing display variety
- **Robust Glass Insulation:** All sides encased in double tempered glass for safety and thermal efficiency
- **Reliable Cooling System:** Ventilating cooling ensures a consistently chilled environment
- **Automatic Defrost Function:** Streamlines upkeep by preventing ice build-up
- **Effective Condensation Removal:** Three-side airducts adeptly manage moisture, keeping the view unobstructed
- **Convenient Access:** Rear sliding doors provide smooth restocking and service
- **Temperature Range:** 2 to + 12
- **Ambient/RH%:** 30/50

Description

Bonvue Chilled Angled Counter-Top Food Display CTA-196

This countertop display unit stands out in the market with its significantly larger display area and an extra shelf, allowing businesses to showcase a greater variety of products prominently.

Key Features

- Eco-Friendly Efficiency: Utilizes natural R290 refrigerant, with an exceptional 9 or 10-star GEMS energy rating
- Enhanced Product Showcase: Offers a larger display area than competitors, featuring an additional shelf for more display space
- Bright LED Lighting: Dual-sided LED lights create an attractive presentation of contents
- Precision Temperature Control: Digital temperature controller for accurate adjustments
- Extra Shelving Advantage: Comes with three adjustable chrome-plated shelves, maximizing display variety
- Robust Glass Insulation: All sides encased in double tempered glass for safety and thermal efficiency
- Reliable Cooling System: Ventilating cooling ensures a consistently chilled environment
- Automatic Defrost Function: Streamlines upkeep by preventing ice build-up
- Effective Condensation Removal: Three-side airducts adeptly manage moisture, keeping the view unobstructed
- Convenient Access: Rear sliding doors provide smooth restocking and service
- Temperature Range: 2 to + 12
- Ambient/RH%: 30/50

1 Year Parts and Labour Warranty

Your Shipping Specifications

Doors	2
Door Type	Sliding Doors
Body	Stainless Steel
Net Weight (Kg)	64
Width (mm)	795
Depth (mm)	560
Height (mm)	874
Packing Width (mm)	630
Packing Depth (mm)	845
Packing Height (mm)	950
Power	240V, 200W/10A
Warranty	1 Year Parts and Labour Warranty